

TRACKER



GEMTECH® ALL RIGHTS RESERVED. For more information visit www.gemtech.com for accessories, adapters, and ammunition. Manufactured by: GEMTECH, PO Box 140618, Boise, ID 83714. Phone: (208) 939-7222. Sales@gemtech.com

WARRANTY AND DISCLAIMER:

READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS.

LIMITED WARRANTY: Gemini Technologies, Inc., DBA Gemtech, warrants to the initial retail purchaser that Gemtech products will be free of defects in workmanship or material and that the product meets manufacturing specifications at the time of manufacture. This warranty is limited to the repair or replacement of the product. This express limited warranty is exclusive and no other express or implied warranty is otherwise provided. GEMTECH MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. Product technical specifications and/or designs may be changed without notice. This warranty does not cover negligence, misuse, careless or improper handling and/or operation, abuse, unauthorized adjustments or modifications, improper mounting/installation, ordinary wear and tear, the failure to follow manufacturer instructions and/or the use of inappropriate or defective ammunition.

GEMTECH SHALL HAVE NO LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES AND UNDER NO CIRCUMSTANCES WILL GEMTECH BE LIABLE FOR PERSONAL INJURY, PROPERTY DAMAGE OR ECONOMIC LOSS.

This warranty and disclaimer is subject to all applicable laws some of which may limit these terms.

WARRANTY REPAIRS: RETURN OF DAMAGED SUPPRESSORS:

If a suppressor is damaged due to a manufacturing defect once it has been fired, it may be returned to Gemtech for repair or replacement. Determination to repair or replace is made solely at our discretion and only after we have had the opportunity to examine and determine that the cause of damage is due to manufacturer defect. It is the responsibility of the customer to cover shipping costs and insurance to return the suppressor to Gemtech for inspection or repair. Gemtech will pay any reasonable shipping and insurance costs to return the unit to you. To ensure proper legal procedures for any repair returns, fill out and provide a copy of the **General Service Form** with any packages sent to us. (Visit: gemtech.com, navigate to CUSTOMER SUPPORT/RETURN & REPAIR POLICIES to download the **General Service Form.pdf** or call 208.939.7222).

BATFE no longer requires transfer on a Form 5 to the manufacturer for repair. BATFE does require a letter accompanying the suppressor detailing the repairs or modifications required. BATFE requires proof of ownership satisfied by a photocopy of the front of the owner's form 3,4, or 5.

NOTE: BATFE prohibits transferring the serial number to a new outer tube in the case of damage to the tube. Tube damage rendering the suppressor unsafe to use will require a new suppressor.



BEFORE USING THIS SUPPRESSOR:

BE CERTAIN YOU HAVE READ AND UNDERSTAND THIS MANUAL. FAILURE TO FOLLOW INSTRUCTIONS IN THIS MANUAL CAN RESULT IN THE POTENTIAL FOR SERIOUS INJURY AND PROPERTY DAMAGE. USE EXTREME CARE AND CAUTION WHEN HANDLING ANY FIREARM AND SUPPRESSOR.

BARREL LENGTHS:

- 24" OR LONGER 300WM
- 16" OR LONGER 7.62X51/.308 WIN
- 16" OR LONGER 5.56X45/.223
- 7.5" OR LONGER 300 BLK

The Tracker is NOT Full Auto rated and intended for hunting purposes only. Must allow suppressor to cool to ambient temperature after 10 rounds (all calibers).

AMMUNITION:

Caliber Rated: 300WM, 7.62 NATO, 5.56 NATO/.223, 300BLK
For the full Supported Caliber List visit: gemtech.com/tracker



ONLY USE FACTORY AMMUNITION MEETING SAAMI SPECIFICATIONS WITH THIS GEMTECH SUPPRESSOR.

Each caliber and ammunition type will have a different sound reduction based on the ammunition velocity, barrel length of the host firearm, and ambient temperature. A muzzle suppressor does not control the velocity of the projectile. High velocity ammunition will be accompanied by the ballistic crack of the bullet in flight if the ammunition is supersonic.

SPECIFICATIONS:

- CALIBER: MULTIPLE, SEE BARREL INFO
- SOUND REDUCTION: 27 dB
- LENGTH: 7.9"
- DIAMETER: 1.6"
- WEIGHT: 11.3 OZ.
- MATERIALS: TITANIUM / ALUMINUM
- FINISH: HARD COAT BLACK ANODIZE
- MOUNT: 5/8-24 (2A) THREAD

Special Note: The Tracker is NOT Full Auto rated and intended for hunting purposes only. Must allow suppressor to cool to ambient temperature after 10 rounds (all calibers).
Factory Ammo Only.



GEMTECH™
WORLD-CLASS SILENCERS™

INSTALLATION AND REMOVAL:



WARNING! DO NOT INSTALL OR REMOVE THE TRACKER WHILE THE FIREARM IS LOADED.

First remove the magazine from the firearm. Second, visually and manually check and clear the chamber and action. Make certain the firearm is unloaded at all times.

INSTALLATION: Remove any thread protector or muzzle device. Thread the suppressor clockwise onto the muzzle.

HAND TIGHTEN ONLY. DO NOT OVER TIGHTEN.

REMOVAL: Unscrew the suppressor by hand. If necessary use a strap wrench on the outside of the suppressor to loosen.

CAUTION! DO NOT REMOVE THE TRACKER WHILE THE SUPPRESSOR IS HOT.

